

Industrial Pressure Washers ...Built Right to Do the Job Right

VHG

Compact, Natural Gas-Heated Hot Water Pressure Washer

- Up to 8.0 GPM, 3000 PSI
- Rugged Belt-Driven Pump with 7-year Warranty
- Electronic Ignition
- LP Conversion Option
- Programmable Smart Control

- Top-of-the-line **Tuff-Skin Hose**, with 24-inch hose guard for burst protection and swivel swedge fitting for twist-free operation, has seven times the abrasion resistance as other high-pressure hoses (hose reel is optional).
- Many Safety Features, including a rupture disk and thermal pump protector to prevent the buildup of excessive pressures or heat.
- High-efficiency burner has Electronic Ignition standard on all models, eliminating the hassle of having to constantly light the pilot flame.
- Hinged Side allows for quick access to components without removing the cabinet.
- Industrial-duty Electric Motor with multiple voltage options and thermal overload protection.

- Extra-durable **Heating Coil** made of leak-free, cold-rolled, Schedule 80 steel pipe with five-year warranty.
- Rugged Steel Frame painted with an epoxy powder-coat finish for all-weather protection (also available in stainless steel option).



- Helpful **Tri-Lingual Labels** with operating instructions in English, Spanish and French for owner and operator protection.
- Our patented Cool-Bypass* system keeps pump water temperature low while in bypass mode.
- Overload protected Control Switches are conveniently located for ease of operation.
- Brass, anti-syphon Detergent Metering Valve locks out air and dispenses precise amount of cleaning agent.
- Industrial-grade, dual belt-driven High-Pressure Pump has a tri-plex, forged brass head with a 7-year limited warranty and U-seals for greater pump protection.
- Four quick-couple **Nozzles**, made of hardened stainless steel, are mounted for ready access.
- Insulated, fatigue-free

 Trigger Gun with chromeplated, dual-lance Variable

 Pressure Wand make for easy
 cleaning and adjusting the



PROGRAMMABLE SMART CONTROL now standard for all VHG machines allows auto start/stop and time delay shutdown features without changing any hardware. It also provides complete control of the equipment run time.

- Rust-free, stainless steel Float Tank with stainless steel inlet filter and low-turbulence float valve allows for high-pressure application of detergent.
- Cast-iron, bushed-bore **Pulleys** with two-bolt adjustment means long life and easy maintenance on the high-pressure pump.
- Consolidated Plumbing has put both the water supply inlet and quick-couple, high-pressure outlet next to each other for ease of installation.

www.landa.com

pressure while washing.



WHY CHOOSE THE VHG?

Compact but heavy duty, this natural gas model's footprint is a mere 24" x 53" for the smallest unit, making it an ideal choice for congested work areas or wash bays where space is at a premium. The small size makes it no less efficient; with cleaning power up to 3000 PSI and 8 GPM, this machine delivers enough cleaning action to tackle a variety of challenges, and includes an optional wireless remote control. The VHG is especially adept at cleaning and maintaining the appearance of the dirtiest fleet or construction equipment.



| Model # | Part # | GPM | PSI | Pump RPM | Pump | Motor HP | Volts | Phase | Amps | Approx BTUs | Ship Wt (lbs) |
|---------------|-------------|-----|------|----------|-----------|----------|-------|-------|------|-------------|---------------|
| VHG4-20024A | 1.109-534.0 | 3.5 | 2000 | 1175 | LM4035R.3 | 5.0 | 230 | 1 | 25 | 364,000 | 750 |
| VHG4-22024A | 1.109-535.0 | 4.0 | 2200 | 835 | LT6036R.2 | 6.2 | 230 | 1 | 27 | 364,000 | 790 |
| VHG4-22024B | 1.109-536.0 | 4.0 | 2200 | 835 | LT6036R.2 | 6.2 | 230 | 3 | 15 | 364,000 | 770 |
| VHG4-22024C | 1.109-537.0 | 4.0 | 2200 | 835 | LT6036R.2 | 6.2 | 460 | 3 | 8 | 364,000 | 780 |
| VHG4-22024G | 1.109-538.0 | 4.0 | 2200 | 835 | LT6036R.2 | 6.2 | 208 | 1 | 29 | 364,000 | 790 |
| VHG4-22024H | 1.109-539.0 | 4.0 | 2200 | 835 | LT6036R.2 | 6.2 | 208 | 3 | 18 | 364,000 | 780 |
| VHG4-30024A | 1.109-541.0 | 3.9 | 3000 | 775 | LT6036R.2 | 8.2 | 230 | 1 | 36 | 354,000 | 868 |
| VHG4-30024B | 1.109-542.0 | 3.9 | 3000 | 775 | LT6036R.2 | 8.2 | 230 | 3 | 25 | 354,000 | 815 |
| VHG4-30024C | 1.109-543.0 | 3.9 | 3000 | 775 | LT6036R.2 | 8.2 | 460 | 3 | 15 | 354,000 | 815 |
| VHG4-30024G | 1.109-544.0 | 3.9 | 3000 | 775 | LT6036R.2 | 8.2 | 208 | 1 | 38 | 354,000 | 815 |
| VHG4-30024H | 1.109-545.0 | 3.9 | 3000 | 775 | LT6036R.2 | 8.2 | 208 | 3 | 27 | 354,000 | 815 |
| VHG5-30024B | 1.109-546.0 | 4.8 | 3000 | 1035 | LT6036R.2 | 10.0 | 230 | 3 | 29 | 480,000 | 780 |
| VHG5-30024C | 1.109-547.0 | 4.8 | 3000 | 1035 | LT6036R.2 | 10.0 | 460 | 3 | 14 | 480,000 | 835 |
| VHG5-30024H | 1.109-548.0 | 4.8 | 3000 | 1035 | LT6036R.2 | 10.0 | 208 | 3 | 30 | 480,000 | 780 |
| VHG6-30024B | 1.109-549.0 | 6.0 | 3000 | 1525 | LT6036L.2 | 15.0 | 230 | 3 | 39 | 507,000 | 1675 |
| VHG6-30024C | 1.109-550.0 | 6.0 | 3000 | 1525 | LT6036L.2 | 15.0 | 460 | 3 | 19 | 507,000 | 1675 |
| VHG8-30024B ‡ | 1.109-552.0 | 8.0 | 3000 | 1370 | LX9536L.2 | 20.0 | 230 | 3 | 52 | 658,000 | 1845 |
| VHG8-30024C ‡ | 1.109-553.0 | 8.0 | 3000 | 1370 | LX9536L.2 | 20.0 | 460 | 3 | 26 | 658,000 | 1845 |

Dimensions: VHG4/VHG5 $53\text{"L} \times 24\text{"W} \times 49\text{"H}$ VHG6/VHG8 $66\text{"L} \times 35\text{"W} \times 62\text{"H}$ ‡ EASY!Force not available on this model.

Field Installed Options & Accessories

| Available for | All Models | Available for Models Up to 5 GPM | | | | |
|--------------------|-----------------------------------|----------------------------------|---------------------------------------|---|--|--|
| 8.903-542.0 | Small Stainless Steel Coil Wrap ◆ | 8.903-543.0 | Wheeled Cart for VHG Propane Model | 8 | | |
| 8.903-546.0 | Large Stainless Steel Coil Wrap ◆ | 9.801-040.0 | Draft Diverter, 10" | 8 | | |
| 8.924-815.0 | Remote Operator Station Kit | 9.801-019.0 | LP Conversion Kit ◆ | 8 | | |
| 8.924-816.0 | Electronic Detergent Kit | 8.903-541.0 | SS Coil Wrap, 4-Panel Skirt & Cover ◆ | (| | |
| 8.924-814.0 | Wireless 6 Channel Remote Kit | | | 8 | | |
| 8.924-878.0 | Wall Mount Remote Bracket Kit | | | 8 | | |
| 9.802-633.0 | LP Gas Regulator Assembly | | | | | |
| • Factory Installe | d | | | | | |

Available for Models Over 5 GPM

8.717-730.0 Draft Diverter, 12" (15 & 20 HP models)
8.904-068.0 LP Conversion Kit (15 & 20 HP models) ◆
8.903-545.0 SS Coil Wrap, 4-Panel Skirt & Cover ◆

Options For Older VHG Units Only [Pre Smart Control]
8.941-545.0 Additional LanCom Remote
8.930-131.0 Wall Mount Bracket for Fixed LC Remote

Distributed by:

DETERGENT FOR EVERY JOB

Landa Kärcher Group's innovative detergent lineup makes your cleaning job easier and faster. Phosphate-free to meet the most stringent environmental demands without sacrificing cleaning effectiveness. We'll match you with a product designed for your specific application.

