

# HOT



## Hot Water Electric Powered Diesel/Oil Heated

The legendary HOT is designed for simple operation, maximum efficiency, and optimal mobility. Its improved design features a stronger frame, larger, flat-free tires, an enclosed motor for longer use, and a more robust burner, all in a hefty yet compact footprint. Simple and affordable with reliable electric-powered hot water delivery, this series is designed for easy operation and servicing as well as portability. Compare the performance and quality of the HOT against any of our rivals, and you will quickly discover its undeniable value.

- Up to 3.5 GPM / 2,000 PSI
- Belt-Drive or Direct-Drive Pump
- Diesel/Oil Heated
- Enclosed 2 HP or 5 HP WEG Motor



Model #	Part #	GPM	PSI	Pump	Pump RPM	Pump	Motor HP	Volts	Phase	Amps	Ship Wt (lbs)
2HOT2-15024D	1.109-177.0	1.9	1500	Direct	1725	LH2126S	2	120	1	20	558
2HOT4-20024A	1.109-178.0	3.5	2000	Belt	1560	LM3840R.3	5	230	1	25	635
2HOT4-20024G	1.109-179.0	3.5	2000	Belt	1560	LM3840R.3	5	208	1	31	635

Dimensions: 52"L x 27"W x 33"H

### Field Installed Options & Accessories

- 8.750-487.0 Pivot Hose Reel (100' capacity, reel only)
- 8.750-477.0 Non-Pivot Hose Reel (100' capacity, reel only)
- 8.917-541.0 Hose Reel Platform with E-Zee Reel & Plumbing (holds 100' of 3/8" hose, not included)\*
- 8.917-522.0 Hose Reel Platform Only\*
- 8.931-584.0 Assembly Float Tank Kit
- 8.931-592.0 Support Rotary Hose Reel Kit (hose reel not included)

\* Should not be used as a lifting rack



**Video Overview**